

## ANTI-MANIPULATION® CYLINDER

### TYPE

### EURO PROFILE CYLINDER

### BENEFIT

Meets the revised requirements  
of PAS24: 2007



Registered  
Kitemark No.  
KM525455

#### Introducing the NEW Anti-manipulation® cylinder

The euro profile cylinder is uniquely protected by 'double sprung' Anti-manipulation® pin tumblers. This ensures that if the cylinder is 'bumped' the 'double sprung' pin tumblers cannot be forced out of the way and entry cannot be gained.

The Anti-manipulation® cylinder has 'Passive' bump resistance. If someone attempts to bump the cylinder the 'double sprung' pin tumblers will block entry without damaging the cylinder. This ensures that the potential intruder is kept out whilst ensuring legitimate key holders can always get in.

The Anti-manipulation® cylinder benefits from a 'semi restricted profile' which ensures keys can not be copied easily. Only approved stockists will have access to key blanks ensuring key control for improved security.

The Anti-manipulation® cylinder has a unique 2 way key operation in normal operation. If a key is left in the cylinder on the inside the lock can still be operated from the outside.



Our Anti-Manipulation cylinder has been approved to BS EN 1303:2005 and carries the following classification.

Category	1	2	3	4	5	6	7	8
Classification	1	6	0	0	0	C	5	2*

**Note:** The Enhanced Security Kitemark Scheme incorporates the additional vulnerability requirements for cylinders covered in BS 3621:2007 and also the following elements of Attack Resistance within EN 1303;

EN 1303: 2005 drill resistance grade 2

EN 1303: 2005 torque resistance of plug/cylinder relevant to attack resistance grade 2, 30Nm

**10**  
YEAR GUARANTEE